

FEATURES

- True sine wave output (THD < 3%)
- RS-232 interface / Remote control port
- Input & output fully isolation
- Thermostatically control cooling fan
- Advanced microprocessor
- Output voltage & frequency switch selectable
- Input polarity reverse / under voltage / over voltage protections
- Output short circuit / overload / over temperature protections
- Built-in Voltage & Wattage meters & LED for power status
- UL / e-13 / CE / FCC approved





	MODEL No.	S1500-112	S1500-124	S1500-148	S1500-212	S1500-224	S1500-248
OUTPUT	AC VOLTAGE	100 / 110 / 120 VAC selectable by DIP switch			220 / 230 / 240 VAC selectable by DIP switch		
	RATED POWER	1500W					
	SURGE POWER	2000W					
	WAVEFORM	True sine wave (THD < 3%)					
	FREQUENCY	50 / 60 Hz selectable by DIP switch					
	AC REGULATION	± 3%					
	POWER FACTOR ALLOWED	COSθ-90°~ COSθ+90°					
	STANDARD RECEPTACLES	NEMA5-15R / GFCI			Schuko / UK / Australia / universal		
	LED INDICATOR	OVP, UVP, OTP, OLPnput voltage level, output load level and fault status					
	INPUT	NO LOAD CURRENT DRAW	0.87A	0.43A	0.23A	0.83A	0.43A
DC VOLTAGE		12VDC	24VDC	48VDC	12VDC	24VDC	48VDC
VOLTAGE RANGE		10.5~15.0VDC	21.0~30.0VDC	42.0~60VDC	10.5~15.0VDC	21.0~30.0VDC	42.0~60VDC
EFFICIENCY (Typ.)		87.0%	90.0%	92.0%	90.0%	93.0%	94.0%
FUSE		35A x 2	20A x 2	10A x 2	35A x 2	20A x 2	10A x 2
REMOTE CONTROL	CR5 optional						
PROTECTION	BAT. LOW ALARM	11VDC	22VDC	44VDC	11VDC	22VDC	44VDC
	BAT. LOW SHUTDOWN	10.5VDC	21.0VDC	42.0VDC	10.5VDC	21.0VDC	42.0VDC
	OVER LOAD	Shut off output voltage, re-power on to recover					
	OVER VOLTAGE	15.3VDC	30.6VDC	61.2VDC	15.3VDC	30.6VDC	61.2VDC
	OVER TEMPERATURE	Shut off output voltage, recovers automatically after temperature goes down					
	OUTPUT SHORT	Shut off output voltage, re-power on to recover					
BAT. POLARITY REVERSE	By fuse open						
ENVIRONMENT	WORKING TEMP.	0 ~ +40°C					
	WORKING HUMIDITY	20% ~ 90% RH non-condensing					
	STORAGE TEMP. & HUMIDITY	-30°C ~ +70°C / -22°F ~ +158°F / 10 ~ 95%					
SAFETY & EMC	SAFETY STANDARDS	UL458 (only for "GFCI" receptacles)			-----		
	ISOLATION RESISTANCE	I/P ~ O/P: 100M Ohms / 500VDC					
	EMI CONDUCTION & RADIATION	Compliance to FCC classA			Compliance to En55022 class A		
	EMS IMMUNITY	-----			Compliance to EN61000-3-2, 3		
	LVD	-----			Compliance to EN60950-1		
	e-MARK	-----			Compliance to e-13 * 72/245/EEC, 95/54/EC		
OTHERS	DIMENSION	390 x 275 x 105mm (L x W x H)					
	PACKING	7.0kgs; 2sets / 18kgs / CARTON					
	COOLING	Thermostatically controlled cooling fan					
	APPLICATION	Home and Office appliances, Power tools and Portable equipments, Vehicle, Yacht and Solar power systems ...etc.					




NEMA 5-15R




North America (GFCI)




Universal



Schuko



Australia
New Zealand



United Kingdom