

Features:

- * 4 stage charging
- * Charger for lead-acid batteries
- * Energy saving mode
- * Front panel indicator for operation status
- * Thermostatically controlled cooling fan
- * Protections: Over voltage / Over temp. / Output short
- Input polarity reverse
- * Approvals: EMC/LVD/e13/CE/SGS/ROHS/ISO 9001



SPECIFICATION

| Automatic Battery Charger | AD-1012 |
|--------------------------------|----------------------------------|
| INPUT RANGE (volt) | 230 AC +/- 10% |
| INPUT FREQUENCY | 50~60 Hz |
| INPUT SOCKET | IEC plug |
| OUTPUT VOLTAGE(volt) | 12 DC |
| Max. OUTPUT POWER | 145W – 10A |
| MULTI-RATE CHARGING FUNCTION | Select by Slide Switch |
| 4 STAGE CHARGING | Soft Start> Builk> Absorp> Maint |
| RECOMMENDED BATTERY CAPACITY | 30Ah~100Ah |
| OVER VOLT PROTECTION | Lower Output Current |
| SHORT CIRCUIT PROTECTION | Yes (by fuse) |
| OVER HEAT PROTECTION | Lower Output Current |
| REVERSE POLARITY PROTECTION | Yes (by fuse) |
| OPERATING TEMPERATURE RANGE(C) | -10 ~ +50 |
| DIMENSION (L*W*H) | 170*72*58mm |
| NET WEIGHT | 0.6 Kg |