



▲ SD-15
78x 51x 28mm



▲ SD-25
99x 97x 36mm



▲ SD-50
159x 97x 38mm

SD-15

Model No.	Wattage	Vin	Vout	Iout	Isolation voltage	Operating temperature	Safety
SD-15A-5	15W	12V (9.2~18V)	5V	3A	1.5KVAC	-10~+60°C	CE / EAC
SD-15A-12			12V	1.25A			
SD-15A-24			24V	0.625A			
SD-15B-5	15W	24V (18~36V)	5V	3A	1.5KVAC	-10~+60°C	CE / EAC
SD-15B-12			12V	1.25A			
SD-15B-24			24V	0.625A			
SD-15C-5	15W	48V (36~72V)	5V	3A	1.5KVAC	-10~+60°C	CE / EAC
SD-15C-12			12V	1.25A			
SD-15C-24			24V	0.625A			

SD-25

Model No.	Wattage	Vin	Vout	Iout	Isolation voltage	Operating temperature	Safety
SD-25A-5	25W	12V (9.2~18V)	5V	5A	1.5KVAC	-10~+60°C	CE / EAC
SD-25A-12	25W		12V	2.1A			
SD-25A-24	26W		24V	1.1A			
SD-25B-5	25W	24V (18~36V)	5V	5A	1.5KVAC	-10~+60°C	CE / EAC
SD-25B-12	25W		12V	2.1A			
SD-25B-24	26W		24V	1.1A			
SD-25C-5	25W	48V (36~72V)	5V	5A	1.5KVAC	-10~+60°C	CE / EAC
SD-25C-12	25W		12V	2.1A			
SD-25C-24	26W		24V	1.1A			

SD-50

Model No.	Wattage	Vin	Vout	Iout	Isolation voltage	Operating temperature	Safety
SD-50A-5	50W	12V (9.2~18V)	5V	10A	1.5KVAC	-10~+60°C	CE / EAC
SD-50A-12			12V	4.2A			
SD-50A-24			24V	2.1A			
SD-50B-5	50W	24V (18~36V)	5V	10A	1.5KVAC	-10~+60°C	CE / EAC
SD-50B-12			12V	4.2A			
SD-50B-24			24V	2.1A			
SD-50C-5	50W	48V (36~72V)	5V	10A	1.5KVAC	-10~+60°C	CE / EAC
SD-50C-12			12V	4.2A			
SD-50C-24			24V	2.1A			