

■ Enclosed Type 15~1000W



▲ RSD-200
191x 86x 40mm



▲ RSD-300
216x 96.5x 40mm

■ RSD-200



Model No.	Wattage	Vin	Vout	Iout	Isolation voltage	Operating temperature	Safety
RSD-200B-12	200W	24V (16.8~31.2V)	12V	16.7A	4KVDC	-40~+70°C	CE (EN50155/EN55032) / EAC
RSD-200B-24	202W		24V	8.4A			
RSD-200B-48	202W		48V	4.2A			
RSD-200C-12	200W	48V (33.6~62.4V)	12V	16.7A	4KVDC	-40~+70°C	CE (EN50155/EN55032) / EAC
RSD-200C-24	202W		24V	8.4A			
RSD-200C-48	202W		48V	4.2A			
RSD-200D-12	200W	96V, 110V (67.2~143V)	12V	16.7A	4KVDC	-40~+70°C	CE (EN50155/EN55032) / EAC
RSD-200D-24	202W		24V	8.4A			
RSD-200D-48	202W		48V	4.2A			

■ RSD-300



Model No.	Wattage	Vin	Vout	Iout	Isolation voltage	Operating temperature	Safety
RSD-300B-5	210W	24V (16.8~31.2V)	5V	42A	4KVDC	-40~+70°C	CE (EN50155/EN55032) / EAC
RSD-300B-12	270W		12V	22.5A			
RSD-300B-24	271W		24V	11.3A			
RSD-300B-48	274W		48V	5.7A			
RSD-300C-5	210W	48V (33.6~62.4V)	5V	42A	4KVDC	-40~+70°C	CE (EN50155/EN55032) / EAC
RSD-300C-12	300W		12V	25A			
RSD-300C-24	300W		24V	12.5A			
RSD-300C-48	302W		48V	6.3A			
RSD-300D-5	210W	96V, 110V (67.2~143V)	5V	42A	4KVDC	-40~+70°C	CE (EN50155/EN55032) / EAC
RSD-300D-12	300W		12V	25A			
RSD-300D-24	300W		24V	12.5A			
RSD-300D-48	302W		48V	6.3A			
RSD-300E-5	210W	36V (25.2~46.8V)	5V	42A	4KVDC	-40~+70°C	CE (EN50155/EN55032) / EAC
RSD-300E-12	300W		12V	25A			
RSD-300E-24	300W		24V	12.5A			
RSD-300E-48	302W		48V	6.3A			
RSD-300F-5	210W	72V (50.4~93.6V)	5V	42A	4KVDC	-40~+70°C	CE (EN50155/EN55032) / EAC
RSD-300F-12	300W		12V	25A			
RSD-300F-24	300W		24V	12.5A			
RSD-300F-48	302W		48V	6.3A			