



▲ RSD-30
113x 60x 25mm



▲ RSD-60
128x 60x 25mm



▲ RSD-100
161x 68x 36mm



▲ RSD-150
189x 77x 36mm

RSD-30



Model No.	Wattage	Vin	Vout	Iout	Isolation voltage	Operating temperature	Safety
RSD-30G-3.3	20W	12V, 24V (9~36V)	3.3V	6A	4KVDC	-40~+70°C	CE (EN50155/EN55032) / EAC
RSD-30G-5	30W		5V	6A			
RSD-30G-12	30W		12V	2.5A			
RSD-30G-24	30W		24V	1.25A			
RSD-30L-3.3	20W	24V, 48V (18~72V)	3.3V	6A	4KVDC	-40~+70°C	CE (EN50155/EN55032) / EAC
RSD-30L-5	30W		5V	6A			
RSD-30L-12	30W		12V	2.5A			
RSD-30L-24	30W		24V	1.25A			
RSD-30H-3.3	20W	96V, 110V (40~160V)	3.3V	6A	4KVDC	-40~+70°C	CE (EN50155/EN55032) / EAC
RSD-30H-5	30W		5V	6A			
RSD-30H-12	30W		12V	2.5A			
RSD-30H-24	30W		24V	1.25A			

RSD-60



Model No.	Wattage	Vin	Vout	Iout	Isolation voltage	Operating temperature	Safety
RSD-60G-3.3	40W	12V, 24V (9~36V)	3.3V	12A	4KVDC	-40~+70°C	CE (EN50155/EN55032) / EAC
RSD-60G-5	60W		5V	12A			
RSD-60G-12	60W		12V	5A			
RSD-60G-24	60W		24V	2.5A			
RSD-60L-3.3	40W	24V, 48V (18~72V)	3.3V	12A	4KVDC	-40~+70°C	CE (EN50155/EN55032) / EAC
RSD-60L-5	60W		5V	12A			
RSD-60L-12	60W		12V	5A			
RSD-60L-24	60W		24V	2.5A			
RSD-60H-3.3	40W	96V, 110V (40~110V)	3.3V	12A	4KVDC	-40~+70°C	CE (EN50155/EN55032) / EAC
RSD-60H-5	60W		5V	12A			
RSD-60H-12	60W		12V	5A			
RSD-60H-24	60W		24V	2.5A			

RSD-100



Model No.	Wattage	Vin	Vout	Iout	Isolation voltage	Operating temperature	Safety
RSD-100B-5	100W	24V (16.8 ~ 31.2V)	5V	20A	4KVDC	-40~+70°C	CE (EN50155/EN55032) / EAC
RSD-100B-12			12V	8.4A			
RSD-100B-24			24V	4.2A			
RSD-100C-5	100W	48V (33.6 ~ 62.4V)	5V	20A	4KVDC	-40~+70°C	CE (EN50155/EN55032) / EAC
RSD-100C-12			12V	8.4A			
RSD-100C-24			24V	4.2A			
RSD-100D-5	100W	96V, 110V (67.2~143V)	5V	20A	4KVDC	-40~+70°C	CE (EN50155/EN55032) / EAC
RSD-100D-12			12V	8.4A			
RSD-100D-24			24V	4.2A			

RSD-150



Model No.	Wattage	Vin	Vout	Iout	Isolation voltage	Operating temperature	Safety
RSD-150B-5	150W	24V (16.8~31.2V)	5V	30A	4KVDC	-40~+70°C	CE (EN50155/EN55032) / EAC
RSD-150B-12	150W		12V	12.5A			
RSD-150B-24	151W		24V	6.3A			
RSD-150C-5	150W	48V (33.6~62.4V)	5V	30A	4KVDC	-40~+70°C	CE (EN50155/EN55032) / EAC
RSD-150C-12	150W		12V	12.5A			
RSD-150C-24	151W		24V	6.3A			
RSD-150D-5	150W	96V, 110V (67.2~143V)	5V	30A	4KVDC	-40~+70°C	CE (EN50155/EN55032) / EAC
RSD-150D-12	150W		12V	12.5A			
RSD-150D-24	151W		24V	6.3A			